240W DIN Rail Type DC-DC Converter

DDR-240 series

User's Manual
Click Me



UL62368-1 AS/NZS62368-1 TPTC004 IEC62368-1

Railway Household Industrial Security Network Telecom

Features

- Compliance to BS EN/EN50155 and BS EN/EN45545-2 railway standard
- Width only 40mm
- 2:1 wide input range
- -40~+70℃ wide working temperature
- 150% peak load capability
- Current sharing up to 960W(3+1)
- DC output adjustable
- Cooling by free air convection
- Can be installed on DIN rail TS-35/7.5 or 15
- Protections: Short circuit / Overload / Over voltage / Over temperature / Input reverse polarity/ Input under voltage protection
- 4KVdc I/O isolation(Reinforced isolation)
- DC OK relay contact
- Remote ON-OFF control
- 3 years warranty

Applications

- Bus,tram,metro or railway system
- Industrial control system
- Semi-conductor fabrication equipment
- Factory automation
- Electro-mechanical
- Wireless network
- Telecom or datacom system

GTIN CODE

MW Search: https://www.meanwell.com/serviceGTIN.aspx

Description

DDR-240 series is a 240W DIN Rail type DC-DC converter with main features including DIN rail-type easy installation, ultra slim width (40mm), 2:1 wide input voltage, fanless design, -40~+70℃ wide operating temperature, 4KVdc I/O isolation, 150% peak load, current sharing,DC OK, adjustable output voltage and full protective functions. This series of models has various input options: 16.8~33.6V / 33.6~67.2V / 67.2~154V and two output options: 24V / 48V and can be used for industrial & railway control, security control, communication system and other fields. Suitable applications include to DC buck/boost regulator, increasing system insulation level and voltage drop compensation along cable...etc.

Model Encoding

DDR - 240 B - 24

- 24 → Output voltage(24/48Vdc)
- B → Input voltage (B:16.8~33.6Vdc, C:33.6~67.2Vdc, D:67.2~154Vdc)
- 240 → Rated wattage
- DDR → Series name

SPECIFICATION

MODEL			DDR-240B-24	DDR-240B-48	DDR-240C-24	DDR-240C-48	DDR-240D-24	DDR-240D-48
OUTPUT	DC VOLTAGE		24V	48V	24V	48V	24V	48v
	RATED CURRENT		10A	5A	10A	5A	10A	5A
	CURRENT RANGE		0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A	0 ~ 10A	0 ~ 5A
	RATED POWER		240W	240W	240W	240W	240W	240W
	PEAK	CURRENT	15A	7.5A	15A	7.5A	15A	7.5A
		POWER Note.5	360W (3sec.)					
	RIPPLE & NOISE (max.) Note.2		80mVp-p	100mVp-p	80mVp-p	100mVp-p	80mVp-p	100mVp-p
	VOLTAGE ADJ. RANGE		24 ~ 28V	48 ~ 56V	24 ~ 28V	48 ~ 56V	24 ~ 28V	48~ 56V
	VOLTAGE TOLERANCE Note.3		±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	LINE REGULATION		±0.5%	±0.5%	±0.5%	±0.5%	±0.5%	±0.5%
	LOAD REGULATION		±1.0%	±1.0%	±1.0%	±1.0%	±1.0%	±1.0%
	SETUP, RISE TIME		500ms, 60ms					
	HOLD UP TIME (Typ.)		Please refer to page 6 Hold up Time(Load de-rating curve)					
INPUT	VOLTAGE RANGE Note.4	CONTINUOUS	16.8 ~ 33.6Vdc		33.6 ~ 67.2Vdc		67.2 ~ 154Vdc	
		100ms	14.4 ~ 16.8Vdc		28.8 ~33.6Vdc		66 ~ 67.2Vdc	
	EFFICIENCY (Typ.)		90%	90%	91%	92%	92%	92.5%
	DC CURRENT (Typ.)		11.2A @24Vdc		5.6A @48Vdc		2.5A @110Vdc	
	INRUSH CURRENT (Typ.)		30A					
	INTERRUPTION OF VOLTAGE SUPPLY		EN50155:2021-Comply with S1 level					
PROTECTION	OVERLOAD Note.5		Normally works within 150% rated output power for more than 3 seconds and then constant current protection 105~135% rated output power with auto-recovery					
	OVER VOLTAGE		28.8 ~ 35V	57.6 ~ 65.0V	28.8 ~ 35V	57.6 ~ 65V	28.8 ~ 35V	57.6 ~ 65V
			Protection type : Shut down o/p voltage, re-power on to recover					
	OVER TEMPERATURE		Shut down o/p voltage, re-power on to recover					
	UNDER VOLTAGE LOCKOUT		24Vin (B - type) :Power ON≥16.8V , OFF≤16.5V		48Vin (C - type) :Power ON≥33.6V , OFF≤33V		110Vin (D - type):Power ON≥67.2V , OFF≤65V	
FUNCTION	DC OK REALY CONTACT RATINGS (max.)		30Vdc/1A resistive load					
	CURRENT SHARING		Up to 960W (3+1 units). Please refer to the Function Manual					
	REMOTE ON-OFF CONTROL		Please refer to the Function Manual					
ENVIRONMENT	WORKING TEMP.		-40 ~ +70℃ (Refer to "Derating Curve")					
	WORKING HUMIDITY		5 ~ 95% RH non-condensing					
	STORAGE TEMP., HUMIDITY		-40 ~ +85, 5 ~ 95% RH non-condensing					
	TEMP. COEFFICIENT		±0.03%/℃ (0 ~ 55℃)					
	VIBRATION		Component:10 ~ 500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes; Mounting: Compliance to IEC61373					
	OPERATING ALTITUDE Note.7		5000 meters					
SAFETY & EMC (Note 6)	SAFETY STANDARDS		IEC 62368-1, UL 62368-1, EAC TP TC 004, AS/NZS 62368.1 approved					
	WITHSTAND VOLTAGE		I/P-O/P:4KVdc I/P-FG:2.5KVdc O/P-FG:0.71KVdc					
	ISOLATION RESISTANCE		I/P-O/P, I/P-FG, O/P-FG:>100M Ohms / 500Vdc / 25℃/ 70% RH					
	EMC EMISSION		**Parameter**		**Standard**		**Test Level / Note**	
			Conducted		BS EN/EN55032		Class B	
			Radiated		BS EN/EN55032		Class B	
			Voltage Flicker		BS EN/EN61000-3-3		----	
			Harmonic Current		----		----	
	EMC IMMUNITY		BS EN/EN55035 , BS EN/EN61000-6-2(BS EN/EN50082-2)					
			Parameter		**Standard**		**Test Level / Note**	
			ESD		BS EN/EN61000-4-2		Level 3, 8KV air ; Level 3, 6KV contact; criteria A	
			Radiated		BS EN/EN61000-4-3		Level 3, 10V/m ; criteria A	
			EFT / Burst		BS EN/EN61000-4-4		Level 3, 2KV ; criteria A	
			Surge		BS EN/EN61000-4-5		Level 3, 1KV/Line-Line ;Level 3, 2KV/Line-Line-FG ;criteria A	
			Conducted		BS EN/EN61000-4-6		Level 3, 10V ; criteria A	
			Magnetic Field		BS EN/EN61000-4-8		Level 4, 30A/m ; criteria A	
	RAILWAY STANDARD		Compliance to BS EN/EN45545-2 for fire protection ; Meet BS EN/EN50155 / IEC60571 including IEC61373 for shock & vibration, BS EN/EN50121-3-2 for EMC					
OTHERS	MTBF		1415.6K hrs min. Telcordia SR-332 (Bellcore) ; 189.9K hrs min. MIL-HDBK-217F (25℃)					
	DIMENSION		40*125.2*113.5mm (W*H*D)					
	PACKING		0.76Kg;20psc/16.2Kg/1.0CUFT					


NOTE

1. All parameters NOT specially mentioned are measured at normal input (B:24Vdc , C:48Vdc , D:110Vdc) , rated load and 25℃ of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1 μF & 47 μF parallel capacitor.
3. Tolerance : includes set up tolerance, line regulation and load regulation.
4. Derating may be needed under low input voltage. Please check the derating curve for more details.
5. 3 seconds max., please refer to peak loading curves.
6. The power supply is considered as an independent unit, but the final equipment still need to re-confirm that the whole system complies with the EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies." (as available on https://www.meanwell.com//Upload/PDF/EMI_statement_en.pdf)
7. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than2000m(6500ft).


※ Product Liability Disclaimer : For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx

■ Block Diagram

fosc : 80KHz




■ Derating Curve



AMBIENT TEMPERATURE (℃)

■ Output derating VS input voltage



B Type:	16.8	21.6	33.6
C Type:	33.6	43.2	67.2
D Type:	67.2	86.4	154

INPUT VOLTAGE (V)

■ Peak Loading

(1)



(2)



■ DC OK Relay Contact

Contact Close	PSU turns on / DC OK.
Contact Open	PSU turns off / DC Fail.
Contact Ratings (max.)	30V/1A resistive load.

■ Function Manual

1. Current sharing


(1) Parallel operation is available by connecting the units shown as below (P+,P- are connected mutually in parallel) :

(2) The voltage difference among each output should be minimized that less than 0.2V is required.

(3) The total output current must not exceed the value determined by the following equation (Output current at parallel operation) =(The rated current per unit) x (Number of unit) x 0.9.

(4) In parallel operation 4 units is the maximum, please consult the manufacture for other applications.

(5) When in parallel operation, the minimum output load should be greater than 3% of total output load. (Min. load > 3% rated current per unit x number of unit)



2. Remote ON-OFF Control

※ The power supply can be turned ON-OFF by using the "Remote ON-OFF" function.

Remote ON-OFF (TB1 PIN2,4)	Output Status
Open or 4 ~ 10VDC	power supply ON
Short or 0 ~ 0.8VDC	power supply OFF

■ Input Fuse


There is one fuse connected in series to the positive input line, which is used to protect against abnormal surge. Fuse specifications of each model are shown as below.

Type	Fuse Type	Reference and Rating
B	Time-Lag	Conquer MST, 10A, 250V *2
C	Time-Lag	Conquer MST, 6.3A, 250V *2
D	Time-Lag	Conquer MST, 6.3A, 250V *1


■ Input Under-Voltage Protection

If input voltage drops below Vimin, the internal control IC shuts down and there is no output voltage. It recovers automatically when input voltage reaches above Vimin,please refer to the cruve below.


DDR-240B-24



DDR-240C-24



DDR-240D-24



■ Input Reverse Polarity Protection

There is a MOSFET connected in series to the negative input line. If the input polarity is connected reversely, the MOSFET opens and there will be no output to protect the unit.


■ Inrush Current

Inrush current is suppressed by a resistor during the initial start-up, and then the resistor is bypassed by a MOSFET to reduce power consumption after accomplishing the start-up.

■ Hold-up Time


Load / Model	100% load	70% load	other load
B type (24Vin)	6ms min.	10ms min.	figure 1,2
C type (48Vin)	8ms min.	11ms min.	figure 3,4
D type (110Vin)	11ms min.	15ms min.	figure 5,6

DDR-240B-24




(figure 1)

DDR-240B-48




(figure 2)

DDR-240C-24




(figure 3)

DDR-240C-48




(figure 4)

DDR-240D-24



(figure 5)

DDR-240D-48




(figure 6)


■ Efficiency vs Load & Vin Curve

The efficiency vs load & Vin curves of each model are shown as below.


DDR-240B-24




DDR-240B-48




DDR-240C-24




DDR-240C-48



DDR-240D-24



DDR-240D-48



■ Immunity to Environmental Conditions

Test method	Standard	Test conditions	Status
Dry Heat Test	EN 50155 section 13.4.5	Temperature: 70℃ / 85℃ Duration: 6 hrs / 10min	PASS
Damp Heat Test, Cyclic	EN 50155 section 13.4.8	Temperature: 25℃~55℃ Humidity: 90%~100% RH Duration: 48 hrs	PASS
Vibration Test	EN 50155 section 13.4.10	Temperature: 19℃ Humidity: 65% Duration: 10 mins	PASS
Shock Test	EN 50155 section 13.4.10	Temperature: 21 ± 3℃ Humidity: 65 ± 5% Duration: 30ms*18	PASS
Low Temperature Storage Test	EN 50155 section 13.4.6	Temperature: -40℃ Dwell Time: 16 hrs	PASS
Salt Mist Test	EN 50155 section 13.4.13	Temperature: 35℃ ±2℃ Duration: 96 hrs	PASS


■ EN45545-2 Fire Test Conditions

Test Items				Hazard Level		
Items			Standard	HL1	HL2	HL3
PCB	R22	Oxygen index test	EN 45545-2:2020 EN ISO 4589-2:2017	PASS	PASS	PASS
		Smoke density test	EN 45545-2:2020 EN ISO 5659-2:2017	PASS	PASS	PASS
		Smoke toxicity test	EN 45545-2:2020 EN 17084:2018	PASS	PASS	PASS
	R24	Oxygen index test	EN 45545-2:2020 EN ISO 4589-2:2017	PASS	PASS	PASS
	R25	Glow-wire test	EN 45545-2:2020 EN 60695-2-11:2014	PASS	PASS	PASS
Potting	R24	Oxygen index test	EN 45545-2:2020 EN ISO 4589-2:2017	PASS	PASS	PASS
Termina; block	R26	Vertical flame test	EN 45545-2:2020 EN 60695-11-10:2013	PASS	PASS	PASS

■ Mechanical Specification

(Unit: mm , tolerance ± 1mm)


Case No.265A-D




Top View

Terminal Pin No. Assignment (TB2,TB3)


Pin No.	Assignment
1,2	DC output +Vo
5,6	DC output -Vo
3,4	DC OK Relay Contact
7,8	P+,P-




Side View



Front View



Side View




Bottom View

Terminal Pin No. Assignment (TB1)

Pin No.	Assignment
1	FG ⏚
2	DC input -Vin
3	DC input +Vin
4	Remote ON/OFF

■ Installation Instruction



ADMISSIBLE DIN-RAIL:TS35/7.5 OR TS35/15

(For reference only. Not included with unit.)

Back View

This series fits DIN rail TS35/7.5 or TS35/15.

For installation details, please refer to the Instruction manual.

■ Installation Manual

Please refer to : http://www.meanwell.com/manual.html