



Features

- Constant Voltage + Constant Current mode output
- Metal housing design with functional Ground
- Built-in active PFC function
- Class 2 power unit
- No load / Standby power consumption <0.5W
- IP67 / IP65 rating for indoor or outdoor installations
- Function options: output adjustable via potentiometer; 3 in 1 dimming (dim-to-off); Smart timer dimming; DALI
- Typical lifetime>50000 hours
- 5 years warranty

Applications

- LED street lighting
- LED architectural lighting
- LED bay lighting
- LED floodlighting
- Type "HL" for use in Class I, Division 2 hazardous (Classified) location.


GTIN CODE

MW Search: <https://www.meanwell.com/serviceGTIN.aspx>

Description

ELG-75 series is a 75W AC/DC LED driver featuring the dual mode constant voltage and constant current output. ELG-75 operates from 100~305VAC and offers models with different rated voltage ranging between 12V and 48V. Thanks to the high efficiency up to 90%, with the fanless design, the entire series is able to operate for -40°C ~ +85°C case temperature under free air convection. The design of metal housing and IP67/IP65 ingress protection level allows this series to fit both indoor and outdoor applications. ELG-75 is equipped with various function options, such as dimming methodologies, so as to provide the optimal design flexibility for LED lighting system

Model Encoding




Type	IP Level	Function	Note
Blank	IP67	Io and Vo fixed.	In Stock
A	IP65	Io and Vo adjustable through built-in potentiometer.	In Stock
B	IP67	3 in 1 dimming function (0~10Vdc, 10V PWM signal and resistance)	In Stock
AB	IP65	Io and Vo adjustable through built-in potentiometer & 3 in 1 dimming function (0~10Vdc, 10V PWM signal and resistance)	In Stock
DA	IP67	DALI control technology.	In Stock

SPECIFICATION

MODEL	ELG-75-12 □		ELG-75-24 □		ELG-75-36 □		ELG-75-42 □		ELG-75-48 □			
OUTPUT	DC VOLTAGE	12V		24V		36V		42V		48V		
	CONSTANT CURRENT REGION Note.2	6 ~ 12V		12 ~ 24V		18 ~ 36V		21 ~ 42V		24 ~ 48V		
	RATED CURRENT	5A		3.15A		2.1A		1.8A		1.6A		
	RATED POWER Note.5	200VAC ~ 305VAC										
		60W		75.6W		75.6W		75.6W		76.8W		
		100VAC ~ 180VAC										
	RATED POWER	48W		60W		60W		60W		60W		
		150mVp-p										
	RIPPLE & NOISE (max.) Note.3	150mVp-p		200mVp-p		250mVp-p		250mVp-p		250mVp-p		
	VOLTAGE ADJ. RANGE	Adjustable for A/AB-Type only (via built-in potentiometer)										
		10.8 ~ 13.2V		21.6 ~ 26.4V		32.4 ~ 39.6V		37.8 ~ 46.2V		43.2 ~ 52.8V		
	CURRENT ADJ. RANGE	Adjustable for A/AB-Type only (via built-in potentiometer)										
		2.5 ~ 5A		1.57 ~ 3.15A		1.05 ~ 2.1A		0.9 ~ 1.8A		0.8 ~ 1.6A		
VOLTAGE TOLERANCE Note.4	±3.0%		±3.0%		±2.5%		±2.5%		±2.0%			
LINE REGULATION	±0.5%		±0.5%		±0.5%		±0.5%		±0.5%			
LOAD REGULATION	±2.0%		±1.0%		±1.0%		±0.5%		±0.5%			
SETUP, RISE TIME Note.6	500ms, 100ms/115VAC, 230VAC											
HOLD UP TIME (Typ.)	10ms/ 230VAC 10ms/ 115VAC(at full load)											
INPUT	VOLTAGE RANGE Note.5	100 ~ 305VAC 142 ~ 431VDC (Please refer to "STATIC CHARACTERISTIC" section)										
	FREQUENCY RANGE	47 ~ 63Hz										
	POWER FACTOR	PF ≥ 0.97/115VAC, PF ≥ 0.95/230VAC, PF ≥ 0.92/277VAC@full load (Please refer to "POWER FACTOR (PF) CHARACTERISTIC" section)										
	TOTAL HARMONIC DISTORTION	THD< 20% (@load≥50%/115VC,230VAC; @load≥75%/277VAC) (Please refer to "TOTAL HARMONIC DISTORTION(THD)" section)										
	EFFICIENCY (Typ.)	86%		88%		89%		90%		90%		
	AC CURRENT	0.7A / 115VAC 0.45A / 230VAC 0.38A/277VAC										
	INRUSH CURRENT(Typ.)	COLD START 50A(twidth=350μs measured at 50% Ipeak) at 230VAC; Per NEMA 410										
	MAX. No. of PSUs on 16A CIRCUIT BREAKER	5 units (circuit breaker of type B) / 8 units (circuit breaker of type C) at 230VAC										
	LEAKAGE CURRENT	<0.75mA / 277VAC										
	NO LOAD / STANDBY POWER CONSUMPTION	No load power consumption <0.5W for Blank / A -Type Standby power consumption <0.5W for B / AB / DA-Type										
	PROTECTION	OVER CURRENT	95 ~ 108% Constant current limiting, recovers automatically after fault condition is removed									
SHORT CIRCUIT		Hiccup mode, recovers automatically after fault condition is removed										
OVER VOLTAGE		14 ~ 18V		28 ~ 34V		41 ~ 48V		47 ~ 54V		54 ~ 62V		
		Shut down output voltage, re-power on to recover										
OVER TEMPERATURE		Shut down output voltage, re-power on to recover										
ENVIRONMENT	WORKING TEMP.	Tcase=-40 ~ +85℃ (Please refer to " OUTPUT LOAD vs TEMPERATURE" section)										
	MAX. CASE TEMP.	Tcase=+85℃										
	WORKING HUMIDITY	20 ~ 95% RH non-condensing										
	STORAGE TEMP., HUMIDITY	-40 ~ +80℃, 10 ~ 95% RH										
	TEMP. COEFFICIENT	±0.03%/℃ (0 ~ 60℃)										
	VIBRATION	10 ~ 500Hz, 5G 12min./1cycle, period for 72min. each along X, Y, Z axes										
SAFETY & EMC	SAFETY STANDARDS	UL8750(type"HL"), CSA C22.2 No. 250.13-12; IEC/BS EN/EN/AS/NZS 61347-1, IEC/BS EN/EN/AS/NZS 61347-2-13 independent, BS EN/EN62384;EAC TP TC 004;BIS IS15885(for 12A/12DA/12B/24A/24B/24DA/36A/36B/42A/42B/48A/48B only); IP65 or IP67; GB/T19510.1, GB/T19510.213; KC61347-1,KC61347-2-13 approved										
	DALI STANDARDS	Compliance to IEC62386-101,102,(207 by request) for DA Type only										
	WITHSTAND VOLTAGE	I/P-O/P:3.75KVAC I/P-FG:2.0KVAC O/P-FG:1.5KVAC										
	ISOLATION RESISTANCE	I/P-O/P, I/P-FG, O/P-FG:100M Ohms / 500VDC / 25℃ / 70% RH										
	EMC EMISSION	Compliance to BS EN/EN55015,BS EN/EN61000-3-2 Class C (@load ≥ 50%) ; BS EN/EN61000-3-3; GB/T 17743, GB17625.1; EAC TP TC 020; KC KN15,KN61547										
	EMC IMMUNITY	Compliance to BS EN/EN61000-4-2,3,4,5,6,8,11; BS EN/EN61547, light industry level (surge immunity Line-Earth 6KV, Line-Line 4KV);EAC TP TC 020; KC KN15, KN61547										
	OTHERS	MTBF	3451.7K hrs min. Telcordia SR-332 (Bellcore) 331.3Khrs min. MIL-HDBK-217F (25℃)									
DIMENSION		180*63*35.5mm (L*W*H)										
PACKING		0.8Kg;16pcs/13.4Kg/0.67CUFT										
NOTE	1. All parameters NOT specially mentioned are measured at 230VAC input, rated current and 25℃ of ambient temperature. 2. Please refer to "DRIVING METHODS OF LED MODULE". 3. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor. 4. Tolerance : includes set up tolerance, line regulation and load regulation. 5. De-rating may be needed under low input voltages. Please refer to "STATIC CHARACTERISTIC" sections for details. 6. Length of set up time is measured at first cold start. Turning ON/OFF the driver may lead to increase of the set up time. 7. The driver is considered as a component that will be operated in combination with final equipment. Since EMC performance will be affected by the complete installation, the final equipment manufacturers must re-qualify EMC Directive on the complete installation again. (as available on https://www.meanwell.com/Upload/PDF/EMI_statement_en.pdf) 8. This series meets the typical life expectancy of >50,000 hours of operation when Tcase, particularly (Tc) point (or TMP, per DLC), is about 70℃ or less. 9. Please refer to the warranty statement on MEAN WELL's website at http://www.meanwell.com 10. The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft). 11. For any application note and IP water proof function installation caution, please refer our user manual before using. https://www.meanwell.com/Upload/PDF/LED_EN.pdf 12. For A/AB type need to consider build in using to comply with Type HL application. ※ Product Liability Disclaimer: For detailed information, please refer to https://www.meanwell.com/serviceDisclaimer.aspx											


File Name:ELG-75-SPEC_2026-07-06

■ Block Diagram



■ DRIVING METHODS OF LED MODULE


- ※ This series is able to work in either Constant Current mode (a direct drive way) or Constant Voltage mode (usually through additional DC/DC driver) to drive the LEDs.



Typical output current normalized by rated current (%)

In the constant current region, the highest voltage at the output of the driver depends on the configuration of the end systems.
Should there be any compatibility issues, please contact MEAN WELL.


DIMMING OPERATION




※ 3 in 1 dimming function (for B/AB-Type)

- Output constant current level can be adjusted by applying one of the three methodologies between DIM+ and DIM-:
0 ~ 10VDC, or 10V PWM signal or resistance.
- Direct connecting to LEDs is suggested. It is not suitable to be used with additional drivers.
- Dimming source current from power supply: 100μA (typ.)


◎ Applying additive 0 ~ 10VDC




"DO NOT connect "DIM- to Vo-"




◎ Applying additive 10V PWM signal (frequency range 100Hz ~ 3KHz):




"DO NOT connect "DIM- to Vo-"



◎ Applying additive resistance:



"DO NOT connect "DIM- to Vo-"





Note : 1. Min. dimming level is about 8% and the output current is not defined when $0\% < I_{out} < 8\%$.

2. The output current could drop down to 0% when dimming input is about 0kΩ or 0Vdc, or 10V PWM signal with 0% duty cycle.


※ DALI Interface (primary side; for DA-Type)

- Apply DALI signal between DA+ and DA-.
- DALI protocol comprises 16 groups and 64 addresses.
- First step is fixed at 8% of output.

■ OUTPUT LOAD vs TEMPERATURE(Note.9)




■ STATIC CHARACTERISTIC



※ De-rating is needed under low input voltage.


■ POWER FACTOR (PF) CHARACTERISTIC

※ Tcase at 75°C



■ TOTAL HARMONIC DISTORTION (THD)


※ 48V Model, Tcase at 75°C




■ EFFICIENCY vs LOAD

ELG-75 series possess superior working efficiency that up to 90% can be reached in field applications.

※ 48V Model, Tcase at 75°C



■ LIFE TIME




■ Mechanical Specification

※ Blank-Type


CASE NO.: 243A

Unit:mm


Tolerance:±1




※ A-Type




※ AB-Type



※ B/DA-Type



※ 3Y Model (3-wire input)



○ Note1: Please connect the case to PE for the complete EMC deliverance and safety use.

○ Note2: Please contact MEAN WELL for input wiring option with PE.

■ Recommend Mounting Direction

